IP---.0802

- Very high wear-resistance
- Fine grained structure
- Easy to weld

Versions of delivery:
Sandblasted (standard) IP---.0802
Sandblasted + fine straightened style IP---.0803

Ordering example: IP 070.0800-2800
I-Profile with inside measurement 70 mm, length 2800 mm)

Dimensions in mm.

Material: Material 18MnNb 6 with plenty more load capacity by add-on of Niob (Nb)
Sizes Available: 60; 70; 80; 90; 110; 120

Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.

General Data

Designation	Weight (kg/m)
IP060.0802	21.00
IP070.0802	19.40
IP080.0802	25.30
IP090.0802	34.00
IP110.0802	40.80
IP120.0802	51.50

Dimensions



Designation	B	D	H	I	T
IP060.0802	72 ±1	14 ±0.5	86.5	62.7 +0.8	12 ±0.5
IP070.0802	65 ±1	9 ±0.5	98	70 +1	14 ±0.5
IP080.0802	66 ±1	11 ±0.5	113.9	77.9 +1	18 ±0.5
IP090.0802	81 ±1.25	12 ±0.5	129.6	88.6 +1	20.5 ±0.5
IP110.0802	83 ±1	14 ±0.5	152.4	108.4 ±0.5	22 ±0.5
IP120.0802	90 ±1.3	15 ±0.5	175 ±0.5	123.8 ±0.5	25.6 ±0.5

Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.