
Heavy Duty Joints 40

Application:

For connecting two profiles at any angle up to $180^{\circ} (\pm 90^{\circ})$. The clamp lever facilitates easy positioning. For heavy duty joints without a clamp lever, the angle can be set by tightening the hexagon nuts.

System: 40 - Slot 8 Type: Joints








SZ1020S




SZ1021N



Rollco A/S • Skomagervej 13 E • 7100 Vejle • Danmark Tel. +45 75 52 26 66 • info@rollco.dk • CVR-nr. 26919010 Page Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice

Heavy Duty Joints 40





SZ1023N

Rollco A/S • Skomagervej 13 E • 7100 Vejle • Danmark Tel. +45 75 52 26 66 • info@rollco.dk • CVR-nr. 26919010 Page Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.

General Data

Designation	Description	System	Material	Weight (g)
SZ1020N	Heavy Duty Joint 40 x 40, natural	40 - Slot 8	GDZn, natural	293
SZ1020S	Heavy Duty Joint 40 x 40, black	40 - Slot 8	GDZn black	293
SZ1021N	Heavy Duty Joint 40 x 40, with clamp lever	40 - Slot 8	GDZn, natural	335
SZ1050N	Heavy Duty Joint 40 x 40, massive, natural	40 - Slot 8	Aluminum, natural anodized	293
SZ1022N	Heavy Duty Joint 40 x 80, natural	40 - Slot 8	GDZn, natural	480
SZ1023N	Heavy Duty Joint 40 x 80, with clamp lever	40 - Slot 8	GDZn, natural	690

Rollco A/S • Skomagervej 13 E • 7100 Vejle • Danmark Tel. +45 75 52 26 66 • info@rollco.dk • CVR-nr. 26919010 Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.